NSN 3020-00-421-8032

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-421-8032

Attachment Method:					
Mounting hole					
Pitch Diameter:					
0.9380 inches					
Teeth Quantity:					
30					
Bore Style:					
Plain both ends					
Mounting Hole Thread Series Designator:					
Unc transversely through hub, first end					
Mounting Hole Thready Qty Per Inch (tpi):					
40 transversely through hub, first end					
Mounting Hole Thread Size:					
0.112 inches transversely through hub, first end					
Mounting Hole Type And Quantity:					
1 threaded transversely through hub, first end					
Outside Diameter:					
1.000 inches					
Nominallength:					
0.500 inches					
Tooth Form:					
Standard					
Pressure Angle:					
20.0000 degrees					
Distance Between Body Face And Protruding Hub End:					
0.375 inches first end					
Face Width:					
0.125 inches					
Bore Diameter:					
0.187 inches both ends					
Hub Style Designator:					
Plain first end					
Hub Diameter:					
0.375 inches first end					
Material:					
Steel comp 303					
Material Specification:					
Qq-s-764, type 303, cond a federal specification single material response					
Surface Treatment:					
Passivate					
Style Designator:					
Protruding hub					

NSN 3020-00-421-8032

Spur Antibacklash Gear - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300