NSN 3020-00-421-8038



Flat Pulley - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-421-8038 **Outside Diameter:** 1.997 inches **Outside Diameter:** 2.040 inches **Thread Size:** 4-40 **Bore Diameter:** 0.625 inches Bore Length: 0.797 inches Flange Width: 0.197 inches and 0.020 inches Flange Quantity: **Securing Hole Quantity: Material And Location:** Aluminum alloy, qq-a-225/8, alloy 6061, t651 Face Width: 0.798 inches **Design Form:** Webbed **Bore Type:** Straight Bearings: Not included **Counterbore Feature:** Not included **Hole Location:** Thru center flange anhub **Keying Facility:** Not included **Securing Method:** Threaded hole **Split Hub Feature:** Not included Web/spoke Relationship To Face Centerline: Offset **Lightening Hole:** Not included

Integral Cooling Vane:

Not included

NSN 3020-00-421-8038 Flat Pulley - Page 2 of 2



Crown Face:
Included
Rim Type:
Solid
Flange Location:
Center and outside
Bore Feature:
Included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Hub End Outside Diameter And Location:
0.625 inches aa end and 0.450 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.176 inches aa end and 0.093 inches bb end
Special Features:
One crowned face, and one flat face, for double belt
Surface Treatment:
Anodized, mil-a-8625, type i, class 1
Style Designator:
Webbed or spoked
Surface Treatment:
Anodized, mil-a-8625, type i, class 1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a