NSN 3020-00-423-6971



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-423-6971 **Outside Diameter:** 20.484 inches **Overall Length:** 3.625 inches **Keyway Width:** Between 0.623 inches and 0.626 inches Thread Size: 5/8-11 **Bore Diameter:** Between 2.4375 inches and 2.4378 inches Bore Length: 3.625 inches **Distance From Center Of Bore To Bottom Of Keyway:** Between 1.5313 inches and 1.5314 inches Pitch Diameter: 19.484 inches **Securing Hole Quantity:** 2 **Furnished Items And Quantity:** Setscrews 2 Face Width: 0.875 inches Guide: Not included **Design Form:** Spoked **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** One hole located on top of keyway, one hole located 120 degrees clockwie from keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole

Not included **Protruding Hub Characteristic:**

Plain

Lightening Hole:

NSN 3020-00-423-6971 Sprocket Wheel - Page 2 of 2



On the transfer
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
37
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.654 inches
Hub End Outside Diameter And Location:
3.750 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
2.563 inches aa end and 0.188 inches bb end
Material:
Steel
Material:
Steel
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c