NSN 3020-00-425-0442

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-425-0442

Outside Diameter: 4.657 inches **Overall Length:** 2.000 inches **Keyway Width:** 0.623 inches **Thread Size:** 1/2-13 **Bore Diameter:** Between 1.688 inches and 1.690 inches **Bore Length:** 2.000 inches Distance From Center Of Bore To Bottom Of Keyway: Between 1.032 inches and 1.033 inches **Pitch Diameter:** 4.179 inches Securing Hole Quantity: 2 **Furnished Items And Quantity:** 2 setscrews Face Width: 0.563 inches **Design Form:** Plain Bore Type: Straight **Metallic Hardness Rating And Location:** 57.000 rockwell c body and 60.000 rockwell c body **Counterbore Feature:** Not included Hole Location: 1 hole located on top of keyway 1 hole located 90 degrees cw from keyway **Keying Facility:** Included Keying Facility Type: Keyway **Securing Method:** Threaded hole **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain

NSN 3020-00-425-0442 Sprocket Wheel - Page 2 of 2



Securing Location:
Aa end or bb end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
13
Asa Standard Chain Number:
80
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 7.000 rockwell c and 60.000 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.000 inches
Distance From Outside Flange/rim To Hub End And Location:
1.344 inches aa end and 3.125 inches aa end
Second End Groove Diameter And Location:
3.375 inches aa end
Material:
Steel
Material:
Steel
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с