NSN 3020-00-425-1608



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-425-1608 **Outside Diameter:** 17.430 inches **Overall Length:** Between 3.740 inches and 3.760 inches **Keyway Width:** Between 0.496 inches and 0.501 inches **Key Width:** Between 0.496 inches and 0.501 inches **Thread Size:** 5/8-11 thd size **Bore Diameter:** Between 2.188 inches and 2.1905 inches **Bore Length:** Between 3.740 inches and 3.760 inches **Distance From Center Of Bore To Bottom Of Keyway:** Between 1.344 inches and 1.34525 inches Pitch Diameter: 16.727 inches **Securing Hole Quantity: Furnished Items And Quantity:** 2 setscrew **Face Width:** 0.688 inches **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** One hole located on top of keyway, one hole located 90 degrees clockwise from keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole **Lightening Hole:**

Aa end

Not included

Securing Location:

NSN 3020-00-425-1608 Sprocket Wheel - Page 2 of 2



Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
42
Asa Standard Chain Number:
100
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.250 inches
Hub End Outside Diameter And Location:
4.000 inches aa end and 3.748 inches bb end and 3.750 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
2.406 inches aa end and 0.085 inches bb end and 0.105 inches bb end
Material:
Steel
Material:
Steel
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Filg:
Г353-с