NSN 3020-00-428-5202

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-428-5202

Outside Diameter:
3.750 inches
Overall Length:
1.000 inches
Bolt Circle Diameter:
2.812 inches
Outside Diameter:
4.125 inches
Bore Diameter:
2.250 inches
Bore Length:
0.062 inches
Flange Width:
0.156 inches
Drilled Hole Diameter:
0.344 inches
Flange Quantity:
2
Securing Hole Quantity:
6
Material And Location:
Material And Location: Steel
Steel
Steel Face Width:
Steel Face Width: 0.750 inches
Steel Face Width: 0.750 inches Design Form:
Steel Face Width: 0.750 inches Design Form: Webbed
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type:
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings:
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature:
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included Hole Location:
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included Hole Location: Axially through hub
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included Hole Location: Axially through hub Keying Facility:
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included Hole Location: Axially through hub Keying Facility: Not included
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included Hole Location: Axially through hub Keying Facility: Not included Securing Method:
Steel Face Width: 0.750 inches Design Form: Webbed Bore Type: Straight Bearings: Not included Counterbore Feature: Not included Hole Location: Axially through hub Keying Facility: Not included Securing Method: Drilled hole

Offset

NSN 3020-00-428-5202 Flat Pulley - Page 2 of 2



Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Crown Face:
Not included
Rim Type:
Solid
Flange Location:
Outside
Bore Feature:
Included
Protruding Hub Characteristic:
Plain
Securing Location:
Pulley surface
Distance From Outside Flange/rim To Hub End And Location:
0.250 inches aa end and 0.938 inches bb end
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a