

View Online at <https://aerobasegroup.com/nsn/3020-00-429-9776>

Groove Depth:

0.875 inches and 0.875 inches

Groove Width:

0.895 inches and 0.895 inches

Overall Length:

14.375 inches

Keyway Width:

0.625 inches

Thread Size:

3/8-18

Bore Length:

6.875 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.609 inches and 1.572 inches

V Groove Angle In Deg:

34.0 and 38.0

Securing Hole Quantity:

1

Face Type:

Step groove

Taper Bore Major Diameter:

2.688 inches

Taper Bore Minor Diameter:

2.616 inches

Material And Location:

Steel

Face Width:

3.250 inches and 9.250 inches

Design Form:

Webbed

Bore Type:

Tapered

Step Quantity:

1

Taper Major Diameter Location:

Bb end

Groove Quantity:

3 or 9

Counterbore Feature:

Not included

Step Outside Diameter:

13.850 inches and 10.313 inches

Hole Location:

In second groove of pulley

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

9c and 3c

Bore Bearing:

Not included

Hub End Outside Diameter And Location:

5.000 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

1.875 inches bb end

V Groove Pitch Diameter:

13.100 inches

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-b