## NSN 3020-00-431-6200

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-431-6200

Attachment Method:
Clamp and mounting hole
Pitch Diameter:
1.2500 inches
Teeth Quantity:
80
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
1.280 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.063 inches second end
Face Width:
0.124 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.430 inches first end
Clamping Surface Length:
0.265 inches first end
Precision Classification:
Quality number 10
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-225/8, t6 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

## NSN 3020-00-431-6200

Spur Antibacklash Gear - Page 2 of 2



Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-a-8625 spec.