NSN 3020-00-431-9288

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-431-9288 **Pitch Diameter:** Between 2.1865 inches and 2.1875 inches **Teeth Quantity:** 105 **Bore Style:** Plain both ends **Outside Diameter:** 2.228 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 hub **Material Specification:** Qq-s-764, cond a federal specification single material response hub **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Mil-std-171, finish no. 5.4.1 military specification single treatment response hub **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No **Fiig**:

A27300

NSN 3020-00-431-9288

Spur Antibacklash Gear - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.