## NSN 3020-00-432-9643

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-432-9643

Counterbore Diameter:
4.250 inches
Counterbore Depth:
1.812 inches
Groove Depth:
0.750 inches
Groove Width:
0.625 inches
Overall Length:
3.187 inches
<b>Bolt Circle Diameter:</b>
3.625 inches
Key Width:
0.312 inches
Thread Size:
7/16-14
Bore Diameter:
1.375 inches
Bore Length:
1.500 inches
Distance From Center Of Bore To Top Of Key:
0.125 inches
V Groove Angle In Deg:
42.0
Securing Hole Quantity:
2
Face Type:
Step groove
Material And Location:
Steel
Face Width:
3.312 inches
Design Form:
Plain
Bore Type:
Straight
Groove Quantity:
3
Counterbore Feature:
Included
Step Outside Diameter:
0.500 in about and 0.405 in about and 0.750 in about

9.500 inches and 8.125 inches and 6.750 inches

## NSN 3020-00-432-9643

Cone Pulley - Page 2 of 2



Counterbore Location:
Bb end
Hole Location:
In body
Keying Facility:
Included
Keying Facility Spacing In Deg:
180.0
Keying Facility Type:
Integral key
Securing Method:
Threaded hole
Split Hub Feature:
Not included
Lightening Hole:
Included
Integral Cooling Vane:
Not included
Groove Shape:
V
Protruding Hub Characteristic:
Plain
Securing Location:
Bb end
Bore Bearing:
Not included
Hub End Outside Diameter And Location:
2.000 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
1.125 inches aa end
V Groove Pitch Diameter:
9.125 inches
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T353-b