## NSN 3020-00-433-1521



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-433-1521 **Outside Diameter:** 15.000 inches **Overall Length:** 6.000 inches **Keyway Width:** 0.750 inches **Thread Size:** 3/4 in.-10 **Bore Diameter:** Between 3.439 inches and 3.441 inches **Bore Length:** 6.000 inches **Distance From Center Of Bore To Bottom Of Keyway:** 2.095 inches and 2.032 inches Pitch Diameter: 13.830 inches **Securing Hole Quantity:** Face Width: 1.250 inches **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Located on bottom of keyway 1.500 in. From hub end **Keying Facility:** Included **Keying Facility Type:** Tapered keyway **Securing Method:** Threaded hole **Lightening Hole:** Not included **Keying Facility Largest Dimension Location:** Bb end **Protruding Hub Characteristic:** 

Plain **Securing Location:** 

Aa end

## **NSN 3020-00-433-1521** Sprocket Wheel - Page 2 of 2



Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
7
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
3.000 inches
Hub End Outside Diameter And Location:
5.500 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
3.000 inches aa end and 1.750 inches bb end
Material:
Steel, fed standard no. 66, aisi or sae 1045
Material:
Steel, fed standard no. 66, aisi or sae 1045
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с