# NSN 3020-00-433-1522

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-433-1522

15.000 inches

## **Overall Length:**

6.000 inches

## Keyway Width:

0.625 inches

#### Thread Size:

3/4 in.-10

#### Bore Diameter:

Between 2.689 inches and 2.691 inches

#### Bore Length:

6.000 inches

#### Distance From Center Of Bore To Bottom Of Keyway:

1.660 inches and 1.596 inches

#### **Pitch Diameter:**

13.830 inches

#### Securing Hole Quantity:

1

#### Face Width:

1.250 inches

#### **Design Form:**

Plain

#### Bore Type:

Straight

#### **Counterbore Feature:**

Not included

#### Hole Location:

Located on bottom of keyway 1.500 in. From hub end

#### **Keying Facility:**

Included

## Keying Facility Type:

Tapered keyway

#### **Securing Method:**

Threaded hole

#### Lightening Hole:

Not included

### Keying Facility Largest Dimension Location:

Bb end

### **Protruding Hub Characteristic:**

Plain

### Securing Location:

Aa end

# NSN 3020-00-433-1522

Sprocket Wheel - Page 2 of 2



Belt/chain/film Size For Which Designed: Roller chain **Roller Chain Pitch Type For Which Designed:** Single pitch **Teeth Row Quantity:** 1 Teeth Quantity Per Row: 7 Hardness Rating Test Method: Not rated **Bore Bearing:** Not included Hub External Keyway: Not included **Tooth Pitch:** 3.000 inches Hub End Outside Diameter And Location: 5.500 inches both ends Distance From Outside Flange/rim To Hub End And Location: 3.000 inches aa end and 1.750 inches bb end Material: Steel, fed standard no. 66, aisi or sae 1045 Material: Steel, fed standard no. 66, aisi or sae 1045 Quantity: 1 Style Designator: Plain Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T353-c