NSN 3020-00-434-8398

Spur Gear - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/3020-00-434-8398

Body Style:
Plain, solid
Pitch Diameter:
1.9000 inches
Teeth Quantity:
19
Bore Style:
W/counterbore both ends
Features Provided:
Casehardened
Outside Diameter:
2.098 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
0.656 inches
Bore Diameter:
1.117 inches both ends
Counterbore Depth:
0.265 inches both ends
Counterbore Diameter:
1.257 inches both ends
Special Features:
Core hardness rockwell c, 28.0 min, 41.0 max
Material:
Steel comp 4620 or steel comp e9310
Material Specification:
Ams 6294 assn standard single material response and ams 6260 assn standard single material response
Surface Treatment:
Copper teeth
Style Designator:
Hubless
Test Data Document:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 3020-00-434-8398 Spur Gear - Page 2 of 2



Fiig:

A27300