NSN 3020-00-437-5636

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-437-5636 **Attachment Method:** Mounting hole Pitch Diameter: 1.0000 inches **Teeth Quantity:** 64 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.0312 inches Nominallength: 0.265 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** 1 groove first end **Hub Diameter:** 0.248 inches first end **First Groove Width:** 0.030 inches first end **First Groove Diameter:** 0.212 inches first end **Distance From End To First Groove:** 0.127 inches first end Material: Steel comp 303 body **Material Specification:** Fed standard 66 federal standard single material response teeth **Surface Treatment:**

Passivate

NSN 3020-00-437-5636

Spur Antibacklash Gear - Page 2 of 2



Surface Treatment Speci

Qq-p-35 federal specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300