## NSN 3020-00-437-5637



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-437-5637 **Attachment Method:** Mounting hole Pitch Diameter: 1.0000 inches **Teeth Quantity:** 64 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.0310 inches Nominallength: 0.241 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.020 inches second end **Face Width:** 0.055 inches **Bore Diameter:** 0.211 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.248 inches first end **First Groove Width:** 0.030 inches first end **First Groove Diameter:** 0.211 inches first end **Distance From End To First Groove:** 

0.191 inches first end

Material:

Steel comp 303 body

## NSN 3020-00-437-5637

Spur Antibacklash Gear - Page 2 of 2



Material Specification
------------------------

Fed standard 66 federal standard single material response teeth

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

Style Designator:

Peripheral face, hubless

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300