NSN 3020-00-437-5637

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-437-5637

Attachment Method:
Mounting hole
Pitch Diameter:
1.0000 inches
Teeth Quantity:
64
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
1.0310 inches
Nominallength:
0.241 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.020 inches second end
Face Width:
0.055 inches
Bore Diameter:
0.211 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
0.248 inches first end
First Groove Width:
0.030 inches first end
First Groove Diameter:
0.211 inches first end
Distance From End To First Groove:
0.191 inches first end
Material:
Steel comp 303 body

NSN 3020-00-437-5637

Spur Antibacklash Gear - Page 2 of 2



Material Specification:

Fed standard 66 federal standard single material response teeth

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Peripheral face, hubless

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300