NSN 3020-00-438-6951

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-438-6951

Body Style:

Plain, solid

Attachment Method:

Mounting hole

Pitch Diameter:

0.7500 inches

Teeth Quantity:

36

Bore Style:

Plain both ends

Backlash Designation:

Grade b

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

32 transversely through hub, first end

Mounting Hole Thread Size:

0.138 inches transversely through hub, first end

Mounting Hole Type And Quantity:

1 plain transversely through hub, first end and 1 threaded transversely through hub, first end

Outside Diameter:

0.791 inches

Nominallength:

0.375 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.250 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.500 inches first end

Precision Classification:

Quality number 8

Mounting Hole Diameter:

0.047 inches transversely through hub, first end

NSN 3020-00-438-6951

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.