## NSN 3020-00-438-6952

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-438-6952

Body Style:

Plain, solid

**Attachment Method:** 

Mounting hole

Pitch Diameter:

0.5625 inches

## **Teeth Quantity:**

27

Bore Style:

Plain both ends

**Backlash Designation:** 

Grade b

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

56 transversely through hub, first end

#### Mounting Hole Thread Size:

0.086 inches transversely through hub, first end

## Mounting Hole Type And Quantity:

1 plain transversely through hub, first end and 1 threaded transversely through hub, first end

Outside Diameter:

0.603 inches

Nominallength:

0.250 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.125 inches first end

Face Width:

0.125 inches

**Bore Diameter:** 

0.250 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.500 inches first end

**Precision Classification:** 

Quality number 8

Mounting Hole Diameter:

0.047 inches transversely through hub, first end

# NSN 3020-00-438-6952

Spur Gear - Page 2 of 2



## Material:

Steel comp 303

## **Material Specification:**

Mil-s-7720, comp 303s military specification single material response

#### **Surface Treatment:**

Passivate

## Surface Treatment Specification:

Mil-f-14072, e300 finish military specification single treatment response

## Style Designator:

Protruding hub

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A27300

## Mil-std (military Standard):

Mil-s-7720 spec.