NSN 3020-00-440-4582

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-440-4582

Attachment Method:
Mounting hole
Teeth Quantity:
74
Bore Style:
Plain both ends
Pitch Radius:
2.7750 inches
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.875 inches first end
Face Width:
0.187 inches
Bore Diameter:
3.125 inches both ends
Hub Style Designator:
1 step first end
Outside Radius:
2.800 inches
End Length:
0.312 inches first end
Precision Classification:
Quality number 6 or quality number 7
End Diameter:
3.344 inches first end
First Step Length:
0.563 inches first end
First Step Diameter:
3.375 inches first end
Arc Length:
5.812 inches
Bolt Hole Circle Diameter:

6.000 inches axially through flange

NSN 3020-00-440-4582

Spur Gear Sector - Page 2 of 2

Material:



Copper alloy 903
Material Specification:
Qq-c-390, alloy d5 federal specification single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-f-495 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-f-495 spec.