NSN 3020-00-441-4869

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-441-4869 **Pitch Diameter:** Between 2.5540 inches and 2.5550 inches **Teeth Quantity:** 184 **Bore Style:** Plain both ends **Outside Diameter:** 2.583 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.500 inches both ends **Hub Style Designator:** Threaded second end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303s or steel comp 303se hub **Material Specification:** Qq-a-268, cond t4 federal specification single material response body **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response hub **Style Designator:** Protruding hubs Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A27300

NSN 3020-00-441-4869

Spur Antibacklash Gear - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.