NSN 3020-00-442-3898

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-442-3898

Webbed, with lightening holes
Pitch Diameter:
1.8125 inches
Teeth Quantity:
58
Bore Style:
Plain both ends
Features Provided:
Casehardened
Outside Diameter:
1.874 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.125 inches first end
Face Width:
0.250 inches
Bore Diameter:
0.4327 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
0.620 inches both ends
Precision Classification:
Quality number 10 or quality number 11
Material:
Steel
Material Specification:
Qq-s-624 comp 4820 cancelled federal specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232 type m, class 2 military specification single treatment response
Style Designator:
One protruding hub, one flush hub
Test Data Document:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 3020-00-442-3898

Spur Gear - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.