## NSN 3020-00-448-5212

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-448-5212 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 6.3333 inches **Teeth Quantity:** 38 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 20 axially through body, first end **Hardness Rating:** 33.0 rockwell c and 39.0 rockwell c **Mounting Hole Thread Size:** 0.250 inches axially through body, first end **Mounting Hole Type And Quantity:** 6 threaded axially through body, first end **Outside Diameter:** 6.664 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Body Recess Depth:** 0.460 inches first end **Face Width:** 0.860 inches **Bore Diameter:** 2.5008 inches both ends **Bolt Hole Circle Diameter:** 3.375 inches axially through body, first end Material:

Steel

**Material Specification:** 

66, aisi/sae 4340 federal standard single material response

**Surface Treatment:** 

Oxide

**Style Designator:** 

Hubless, recessed body

## NSN 3020-00-448-5212

Spur Gear - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300