

View Online at <https://aerobasegroup.com/nsn/3020-00-451-0291>

Groove Depth:

0.545 inches

Groove Width:

0.550 inches

Outside Diameter:

9.000 inches

Overall Length:

1.512 inches

Bolt Circle Diameter:

3.625 inches

Keyway Width:

0.188 inches

Thread Size:

3/8-16

Bore Diameter:

1.109 inches

Bore Length:

1.306 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.277 inches

V Groove Angle In Deg:

20.0

Pitch Diameter:

7.910 inches

Securing Hole Quantity:

2

Material And Location:

Iron, cast

Face Width:

0.978 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

One above keyway, one below keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Pulley surface

Hub End Outside Diameter And Location:

2.078 inches aa end and 2.055 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.195 inches aa end and 0.744 inches bb end

First Step Length And Location:

0.445 inches aa end

Hub End Outside Diameter And Location:

0.768 inches aa end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a