## NSN 3020-00-451-6303

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-451-6303 **Body Style:** Plain, solid Pitch Diameter: 3.8330 inches **Teeth Quantity:** 23 **Bore Style:** Plain both ends **Outside Diameter:** 4.100 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 1.000 inches first end **Face Width:** 0.500 inches **Bore Diameter:** 0.500 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 1.500 inches first end **Precision Classification:** Quality number 6 **Special Features:** Hub is slotted with 0.062 sawcut crosswise 0.312 from face of hub to a depth of 1.250 in and face of gear is drilled on a 0.500 in bolt circle diameter through the gear 0.281 drill and a0.438 countersink to accept a 0.250-20 bolt Material: Aluminum alloy 6061 **Material Specification:** Qq-a-250/11, t6 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-8625, type 2 military specification single treatment response **Style Designator:** 

--

N/a

Protruding hub
Shelf Life:

**Unit Of Measure:** 

## NSN 3020-00-451-6303

Spur Gear - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A27300

Mil-std (military Standard):

spec.