

View Online at <https://aerobasegroup.com/nsn/3020-00-451-7966>

**Counterbore Diameter:**

2.000 inches

**Counterbore Depth:**

0.100 inches

**Groove Depth:**

0.500 inches

**Groove Width:**

0.403 inches

**Outside Diameter:**

5.600 inches

**Overall Length:**

2.660 inches

**Keyway Width:**

0.189 inches

**Bore Diameter:**

1.188 inches

**Bore Length:**

0.840 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.636 inches

**V Groove Angle In Deg:**

18.0

**Pitch Diameter:**

5.000 inches

**Material And Location:**

Iron, g-13m, general motors corporation

**Face Width:**

1.820 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Included

**Counterbore Location:**

Bb end

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

A

**Bore Feature:**

Included

**Hub End Outside Diameter And Location:**

1.620 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.840 inches aa end and 1.820 inches bb end

**Special Features:**

Integral counterweight on pulley

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-a