

View Online at <https://aerobasegroup.com/nsn/3020-00-454-8241>

**Counterbore Diameter:**

Between 4.812 inches and 4.816 inches

**Counterbore Depth:**

0.250 inches

**Groove Depth:**

0.323 inches

**Groove Width:**

0.441 inches

**Outside Diameter:**

Between 12.079 inches and 12.119 inches

**Bolt Circle Diameter:**

4.125 inches

**Bore Diameter:**

3.500 inches

**Bore Length:**

0.250 inches

**Drilled Hole Diameter:**

Between 0.406 inches and 0.416 inches

**V Groove Angle In Deg:**

62.0

**Pitch Diameter:**

Between 11.525 inches and 11.535 inches

**Securing Hole Quantity:**

8

**Material And Location:**

Aluminum alloy, mil-a-21180, a356 or c355, class 1, 2, or 3, grade d,

**Face Width:**

2.186 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

4

**Counterbore Feature:**

Included

**Counterbore Location:**

Aa end

**Hole Location:**

On hub face

**Keying Facility:**

Not included

**Securing Method:**

Drilled hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

5.250 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.626 inches bb end

**Surface Treatment:**

Anodic, mil-a-8625, type 3, class 1,

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Anodic, mil-a-8625, type 3, class 1,

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a