## NSN 3020-00-455-1225

Shelf Life:

N/a

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-455-1225

Attachment Method:
Mounting hole
Pitch Diameter:
0.9375 inches
Teeth Quantity:
60
Bore Style:
Plain both ends
Outside Diameter:
0.9688 inches
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10 or quality number 11
Special Features:
Two threaded mtg holes located hub between hub end and gear face 90 degrees apart; unc thread series; mtg hole nom thd size 0.112 in.
40 thds per in.
Material:
Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 316 hub
Material Specification:
Qq-a-225/6 federal specification single material response body
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response hub
Style Designator:
Protruding hub

## NSN 3020-00-455-1225

Spur Antibacklash Gear - Page 2 of 2



	• -		
In	ıŧ	( )t	Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.