## NSN 3020-00-455-2928



Spur Gear - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/3020-00-455-2928	
Body Style:	
Webbed, offset, solid	
Attachment Method:	
Mounting hole	
Pitch Diameter:	
6.8333 inches	
Teeth Quantity:	
82	
Bore Style:	
Plain both ends	
Mounting Hole Type And Quantity:	
8 plain axially through body, first end	
Outside Diameter:	
7.000 inches	
Tooth Form:	
Stub	
Pressure Angle:	
20.0000 degrees	
Distance Between Body Face And Protruding Hub End:	
1.016 inches first end	
Face Width:	
0.312 inches	
Bore Diameter:	
4.000 inches both ends	
Hub Style Designator:	
1 groove first end	
Hub Diameter:	
4.6205 inches first end	
First Groove Width:	
0.1725 inches first end	
First Groove Diameter:	
4.4010 inches first end	
Distance From End To First Groove:	
0.2400 inches first end	
Mounting Hole Diameter:	

**Mounting Hole Diameter:** 

0.265 inches axially through body, first end

Material:

Steel

**Material Specification:** 

Ams-5643 assn standard single material response

**Surface Treatment:** 

Oxide

## NSN 3020-00-455-2928

Spur Gear - Page 2 of 2



Mil-c-13924 military specification single treatment response

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-c-13924 spec.