NSN 3020-00-455-9289



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-455-9289 **Attachment Method:** Mounting hole Pitch Diameter: 3.0000 inches **Teeth Quantity:** 144 **Bore Style:** Plain both ends **Outside Diameter:** 3.0417 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.563 inches first end **Special Features:** Hole location hub between hub end and gear face 90 degrees apart; mounting hole nom diameter 0.063 in., type plain qty1 and threaded q type 1, thread series designator unc, nom thread size 0.112 in., thread qty per in. 40 Material: Steel hub **Material Specification:** Mil-s-7720, comp 303 military specification single material response hub **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response

N/a

Style Designator: Protruding hub Shelf Life:

Unit Of Measure:

NSN 3020-00-455-9289

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.