NSN 3020-00-457-7022

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-457-7022 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.7330 inches and 0.7340 inches **Teeth Quantity:** 47 **Bore Style:** Plain both ends Hardness Rating: 34.0 rockwell c and 38.0 rockwell c hub **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end **Outside Diameter:** 0.771 inches Nominallength: 0.275 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.165 inches first end **Face Width:** 0.110 inches **Bore Diameter:** 0.124 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.245 inches first end **Mounting Hole Diameter:** 0.025 inches transversely through hub, first end Material: Steel **Material Specification:** Mil-s-6709 military specification single material response **Style Designator:** Protruding hub

N/a

Shelf Life:

NSN 3020-00-457-7022

Spur Gear - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-6709 spec.