## NSN 3020-00-458-4544

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-458-4544 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.2073 inches and 0.2083 inches **Teeth Quantity:** 20 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc axially through flange Mounting Hole Thready Qty Per Inch (tpi): 56 axially through flange **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded axially through flange **Outside Diameter:** 0.228 inches **Tooth Form:** Standard Flange Diameter: 0.250 inches **Pressure Angle:** 20.0000 degrees Flange Thickness: 0.125 inches **Face Width:** 0.094 inches **Bore Diameter:** 0.125 inches both ends **Distance Between Outer Body Face And Inner Flange Face:** 0.125 inches **Hub Style Designator:** 

Plain first end

**Hub Diameter:** 

0.188 inches first end

Material:

Steel comp 303se

## **Material Specification:**

Qq-s-764, type 303se, cond a federal specification single material response

## NSN 3020-00-458-4544

Spur Gear - Page 2 of 2



$\overline{}$			-			
<b>~</b> I	ırfa	ഫ	ırc	natr	nΔn	

Passivate

Style Designator:

Flanged end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300