
NSN 3020-00-463-0746

Spur Gear - Page 1 of 2





Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** Between 0.8115 inches and 0.8125 inches **Teeth Quantity:** 39 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end Mounting Hole Thread Size: 0.138 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.853 inches Nominallength: 0.437 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end Face Width: 0.187 inches **Bore Diameter:** 0.375 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.625 inches first end Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303 federal specification single material response Surface Treatment: Passivate

NSN 3020-00-463-0746

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300

