
## NSN 3020-00-465-2846

Spur Gear - Page 1 of 2





**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** Between 1.9990 inches and 2.0000 inches **Teeth Quantity:** 144 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end Mounting Hole Thread Size: 0.138 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 2.026 inches Nominallength: 0.375 inches Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.313 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.880 inches first end Material: Steel comp 416 **Material Specification:** Qq-s-764, type 416 cond a federal specification single material response Surface Treatment: Passivate Style Designator: Protruding hub

## NSN 3020-00-465-2846

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

