## NSN 3020-00-465-2888

Sprocket Wheel - Page 1 of 2

**Outside Diameter:** 



View Online at https://aerobasegroup.com/nsn/3020-00-465-2888

1.570 inches
Overall Length:
0.500 inches
Keyway Width:
0.125 inches
Thread Size:
No. 8-32
Bore Diameter:
0.500 inches
Bore Length:
0.500 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.312 inches
Pitch Diameter:
1.440 inches
Securing Hole Quantity:
1
Face Width:
0.110 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Located on top of key
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Threaded hole
Lightening Hole:
Not included
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain

## **NSN 3020-00-465-2888** Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
18
Asa Standard Chain Number:
25
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.250 inches
Hub End Outside Diameter And Location:
1.125 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.390 inches aa end
Material:
Steel, qq-s-764, type 303, cond a-canceled
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a-canceled federal specification single material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
T353-c