NSN 3020-00-467-5223

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-467-5223

Outside Diameter:
2.288 inches
Keyway Width:
0.188 inches
Bore Diameter:
0.875 inches
Bore Length:
0.719 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.531 inches
Pitch Diameter:
2.280 inches
Face Width:
0.719 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
50.0 rockwell c body
Counterbore Feature:
Not included
Groove Position:
N/a
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Split-tapered bushing
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Silent chain
Teeth Row Quantity:
1
Teeth Quantity Per Row:
19
Asa Standard Chain Number:
100

NSN 3020-00-467-5223

Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method: Rockwell Teeth Hardness Rating: A.C scale, 50 hardness of teeth Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.375 inches

Material:

Steel, qq-s-633, comp c1045-canceled

Material:

Steel comp 1045

Material Specification:

Qq-s-633, comp c1045-canceled federal specification single material response

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

Т353-с