# NSN 3020-00-468-3170

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-468-3170

#### **Outside Diameter:**

1.932 inches

#### **Overall Length:**

0.310 inches

#### Thread Size:

0.138-32

#### Bore Diameter:

0.250 inches

### Bore Length:

0.313 inches

#### Pitch Diameter:

1.973 inches

#### Securing Hole Quantity:

1

# Furnished Items And Quantity:

# Setscrew, one each

Face Width:

#### 0.065 inches

Guide:

#### Not included

**Design Form:** 

#### Plain

Bore Type:

#### Straight

**Counterbore Feature:** 

Not included

Hole Location:

Centered 0.125 in. From end of hub

#### Keying Facility:

Not included

#### Securing Method:

Threaded hole

#### Lightening Hole:

Not included

# Protruding Hub Characteristic:

Plain

## Securing Location:

Aa end

#### Belt/chain/film Size For Which Designed:

Silent chain

#### **Teeth Row Quantity:**

1

# **NSN 3020-00-468-3170** Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
33
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.1875 inches
Hub End Outside Diameter And Location:
0.625 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.250 inches aa end
Material:
Steel, mil-s-16782-canceled
Material:
Steel comp 1010 or steel comp 1015
Material Specification:
Mil-s-16782-canceled military specification single material response
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с
Mil-std (military Standard):
Mil-s-16782-canceled spec.