NSN 3020-00-468-4732

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-468-4732

Body Style: Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.4970 inches and 0.4990 inches **Teeth Quantity:** 24 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 36 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.540 inches Nominallength: 0.250 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end **Face Width:** 0.094 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.375 inches first end **Special Features:**

Threaded holes spaced 90 degrees apart

Material:

Copper alloy 922

Material Specification:

Qq-c-390, alloy d4 federal specification single material response

NSN 3020-00-468-4732

Spur Gear - Page 2 of 2



Stv	le l	Des	ian	ator:	

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300