NSN 3020-00-469-6975

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-469-6975

View Online at https://aerobasegroup.com/nsn/3020-00-469-6975
Outside Diameter:
7.500 inches
Overall Length:
3.125 inches
Keyway Width:
Between 0.874 inches and 0.875 inches
Thread Size:
5/8 in11
Bore Diameter:
Between 3.626 inches and 3.628 inches
Bore Length:
3.125 inches
Distance From Center Of Bore To Bottom Of Keyway:
1.950 inches
Pitch Diameter:
6.910 inches
Securing Hole Quantity:
1
Face Width:
0.812 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Located on hub on top of keyway
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Threaded hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end

NSN 3020-00-469-6975

Sprocket Wheel - Page 2 of 2



Belt/chain/film Size For Which Designed:

Silent chain

Teeth Row Quantity:

1

Teeth Quantity Per Row:

13

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

1.654 inches

Hub End Outside Diameter And Location:

5.000 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

1.469 inches aa end and 0.844 inches bb end

Material:

Steel, aisi 1045 or steel, sae 1045 or steel, aisi 1017 or steel, sae 1017

Material:

Steel comp 1045 or steel comp 1045 or steel comp 1017 or steel comp 1017

Material Specification:

Aisi 1045 assn standard 1st material response and sae 1045 assn standard 2nd material response and aisi 1017 assn standard 3rd material

response and sae 1017 assn standard 4th material response

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

T353-c