

View Online at <https://aerobasegroup.com/nsn/3020-00-469-9889>

**Groove Depth:**

0.813 inches

**Groove Width:**

0.813 inches

**Outside Diameter:**

7.500 inches

**Overall Length:**

3.375 inches

**Bolt Circle Diameter:**

5.000 inches

**Keyway Width:**

Between 0.376 inches and 0.378 inches

**Bore Diameter:**

Between 2.000 inches and 2.001 inches

**Bore Length:**

3.375 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 1.175 inches and 1.180 inches

**Drilled Hole Diameter:**

0.453125 inches

**V Groove Angle In Deg:**

38.0

**Securing Hole Quantity:**

6

**Material And Location:**

Iron, cast, sae 110

**Face Width:**

1.000 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

1

**Counterbore Feature:**

Not included

**Hole Location:**

Located on portion of pulley between hub and pulley groove

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Drilled hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Stepped

**Hub End Outside Diameter And Location:**

2.875 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.938 inches bb end and 1.438 inches aa end

**First Step Face Largest Diameter And Location:**

3.000 inches both ends

**First Step Length And Location:**

0.688 inches both ends

**Third Step Face Largest Diameter And Location:**

0.938 inches both ends

**Hub End Outside Diameter And Location:**

2.875 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.938 inches aa end

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a