

View Online at <https://aerobasegroup.com/nsn/3020-00-469-9889>

Groove Depth:

0.813 inches

Groove Width:

0.813 inches

Outside Diameter:

7.500 inches

Overall Length:

3.375 inches

Bolt Circle Diameter:

5.000 inches

Keyway Width:

Between 0.376 inches and 0.378 inches

Bore Diameter:

Between 2.000 inches and 2.001 inches

Bore Length:

3.375 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 1.175 inches and 1.180 inches

Drilled Hole Diameter:

0.453125 inches

V Groove Angle In Deg:

38.0

Securing Hole Quantity:

6

Material And Location:

Iron, cast, sae 110

Face Width:

1.000 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

Located on portion of pulley between hub and pulley groove

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Hub End Outside Diameter And Location:

2.875 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.938 inches bb end and 1.438 inches aa end

First Step Face Largest Diameter And Location:

3.000 inches both ends

First Step Length And Location:

0.688 inches both ends

Third Step Face Largest Diameter And Location:

0.938 inches both ends

Hub End Outside Diameter And Location:

2.875 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.938 inches aa end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a