NSN 3020-00-474-0096

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-474-0096

| Outside Diameter: |
|--|
| 0.825 inches |
| Overall Length: |
| 0.375 inches |
| Thread Size: |
| No. 4/0.112/ in40 |
| Bore Diameter: |
| 0.252 inches |
| Bore Length: |
| 0.375 inches |
| Pitch Diameter: |
| 0.745 inches |
| Securing Hole Quantity: |
| 2 |
| Face Width: |
| 0.065 inches |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Hole Location: |
| One located onhub portion of sprocket between hub end and face |
| Keying Facility: |
| Not included |
| Securing Method: |
| Threaded hole |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Grooved |
| Groove/step Location: |
| Aa end |
| Securing Location: |
| Aa end |
| Belt/chain/film Size For Which Designed: |
| Roller chain |
| Roller Chain Pitch Type For Which Designed: |
| Single pitch |
| Teeth Row Quantity: |

NSN 3020-00-474-0096 Sprocket Wheel - Page 2 of 2



| Teeth Quantity Per Row: |
|---|
| 16 |
| Hardness Rating Test Method: |
| Not rated |
| Bore Bearing: |
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 0.148 inches |
| Hub End Outside Diameter And Location: |
| 0.437 inches both ends and 0.600 inches bb end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.030 inches bb end and 0.280 inches both ends |
| First Step Face Largest Diameter And Location: |
| 0.600 inches both ends |
| First Step Length And Location: |
| 0.250 inches both ends |
| Material: |
| Steel |
| Material: |
| Steel |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Passivated |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-c |
| |