NSN 3020-00-478-3536

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-478-3536

Body Style:

Plain, solid

Attachment Method:

Clamp

Pitch Diameter:

2.1000 inches

Teeth Quantity:

168

Bore Style:

Plain both ends

Outside Diameter:

2.122 inches

Nominallength:

0.295 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.245 inches first end

Face Width:

0.045 inches

Bore Diameter:

0.125 inches both ends

Hub Style Designator:

Split first end

Hub Diameter:

0.248 inches first end

Clamping Surface Length:

0.155 inches first end

Precision Classification:

Quality number 12

Special Features:

Yone hole dia. 0.048 in. Located on vertical axis 0.225 in. From center, one hole dia. 0.095 in. Located 0.095 in. Along horizontal axis from center and 0.205 in. From center along vertical axis, teeth and bore have microinch finish 32

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

NSN 3020-00-478-3536

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

