NSN 3020-00-479-2502

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-479-2502

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
6.2500 inches
Teeth Quantity:
75
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unf axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through hub, first end
Hardness Rating:
81.0 rockwell a and 85.0 rockwell a teeth
Mounting Hole Thread Size:
0.190 inches axially through hub, first end
Mounting Hole Type And Quantity:
18 threaded axially through hub, first end
Outside Diameter:
6.512 inches
Nominallength:
1.376 inches
Tooth Form:
Standard
Pressure Angle:
22.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.288 inches first end
Face Width:
0.840 inches
Bore Diameter:
5.030 inches both ends
Counterbore Depth:
0.440 inches both ends
Counterbore Diameter:
5.140 inches both ends
Hub Style Designator:
1 step both ends
End Length:
0.007 inches both ends

NSN 3020-00-479-2502 Spur Gear - Page 2 of 2



End Diameter:
5.738 inches first end
First Step Length:
0.281 inches both ends
First Step Diameter:
6.140 inches both ends
Bolt Hole Circle Diameter:
5.345 inches axially through hub, first end
Material:
Steel comp e9310
Material Specification:
Ams 6260 assn standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300