NSN 3020-00-482-8196

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-482-8196

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Clamp |
| Pitch Diameter: |
| 2.1875 inches |
| Teeth Quantity: |
| 70 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 2.250 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.281 inches first end |
| Face Width: |
| 0.063 inches |
| Bore Diameter: |
| 0.125 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.186 inches first end |
| Clamping Surface Length: |
| 0.250 inches first end |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-225/8 t6 federal specification single material response |
| Surface Treatment: |
| Oxide film |
| Surface Treatment Specification: |
| Mil-c-5541, type 2, grade c, class 3 military specification single treatment response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-482-8196

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.