## NSN 3020-00-483-1120

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-483-1120

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.5469 inches
Teeth Quantity:
99
Bore Style:
Plain first end
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 axially through hub, first end
Mounting Hole Thread Size:
0.112 inches axially through hub, first end
Mounting Hole Type And Quantity:
1 threaded axially through hub, first end
Nominallength:
0.255 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.162 inches first end
Hub Style Designator:
Pinned first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10 or quality number 11
Special Features:
Outside diameter 1.5761min 1.5781max in.; bore provision included; bore diameter 0.1871min 0.1877max in.; bore length 0.255 in.; face
width 0.088min 0.098max in.; first end distance from end of hub to center of tapped hole 0.078 in.; circular pitch 0.04909 in.
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, alloy 2024, t4 federal specification single material response
Surface Treatment:
Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 2, class 1 military specification single treatment response

## NSN 3020-00-483-1120

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-a-8625 spec.