NSN 3020-00-486-8695

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-486-8695

Body Style:
Webbed, solid
Spline Quantity:
16 both ends
Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.4990 inches and 2.5000 inches
Teeth Quantity:
40
Bore Style:
Plain both ends
Spline Pitch Diameter:
0.4990 inches both ends and 0.5000 inches both ends
Hardness Rating:
30.0 rockwell c and 35.0 rockwell c hub
Mounting Hole Type And Quantity:
4 plain axially through body, first end
Outside Diameter:
2.622 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
1.365 inches first end
Face Width:
0.220 inches
Bore Diameter:
0.561 inches both ends
Hub Style Designator:
2 steps first end
End Length:
0.590 inches first end
End Diameter:
0.984 inches second end
First Step Length:
0.600 inches first end
First Step Diameter:
1.090 inches second end
Second Step Length:

0.175 inches first end

NSN 3020-00-486-8695 Spur Gear - Page 2 of 2



Second Step Diameter:
1.030 inches first end
Mounting Hole Diameter:
0.250 inches axially through body, first end
Bolt Hole Circle Diameter:
1.500 inches axially through body, first end
Special Features:
Counterbore on 2nd end, 0.749 in. Diameter by 0.810 in. Dep
Material:
Steel comp 4140
Material Specification:
Fed standard 66 federal standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A27300