NSN 3020-00-493-1887

Sprocket Wheel - Page 1 of 2

Counterbore Diameter:

Counterbore Depth:

Outside Diameter:

5.000 inches

0.228 inches

10.460 inches



View Online at https://aerobasegroup.com/nsn/3020-00-493-1887

Keyway Width:
0.188 inches
Bore Length:
2.228 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.920 inches
Pitch Diameter:
0.036 inches
aper Bore Major Diameter:
.495 inches
aper Bore Minor Diameter:
.329 inches
Face Width:
2.228 inches
Design Form:
Plain
Bore Type:
Tapered Tapere
Metallic Hardness Rating And Location:
25.0 rockwell c hub
Counterbore Feature:
ncluded
Counterbore Location:
Aa end
Keying Facility:
ncluded
Keying Facility Type:
apered keyway
Securing Method:
Any acceptable
ightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch

NSN 3020-00-493-1887 Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
3
Center To Center Distance Between Teeth Rows:
0.892 inches
Teeth Quantity Per Row:
42
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 40.0 rockwell c and 45.0 rockwell c
Bore Bearing:
Not included
Tooth Pitch:
0.750 inches
Material:
Steel, sae 1045
Material:
Steel comp 1045
Material Specification:
Sae 1045 assn standard single material response
Quantity:
1
Style Designator:
Plain
Surface Treatment:
Any acceptable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c