NSN 3020-00-494-2872

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-494-2872

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.4652 inches and 0.4667 inches
Teeth Quantity:
60
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
72 transversely through hub, first end
Hardness Rating:
28.0 rockwell c and 32.0 rockwell c teeth
Mounting Hole Thread Size:
0.073 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.482 inches
Nominallength:
0.156 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.125 inches first end
Face Width:
0.031 inches
Bore Diameter:
0.093 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.218 inches first end
Material:
Steel comp 416
Material Specification:
Qq-s-764, type 416 cond a federal specification single material response

NSN 3020-00-494-2872

Spur Gear - Page 2 of 2



•	_			
Style	1)6	SIM	na	t∩r∙
Otylo		JIG	ııu	w.

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300