NSN 3020-00-495-9614

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-495-9614 **Groove Depth:** 0.406 inches and 0.562 inches **Groove Width:** 0.438 inches and 0.625 inches **Overall Length:** 1.688 inches **Keyway Width:** 0.188 inches **Bore Diameter:** 1.000 inches **Bore Length:** 1.031 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.656 inches V Groove Angle In Deg: 20.0 Face Type: Step groove **Material And Location:** Steel Face Width: 0.562 inches and 0.875 inches **Design Form:** Webbed **Bore Type:** Straight Step Quantity: **Groove Quantity: Counterbore Feature:** Not included **Step Outside Diameter:** 5.000 inches and 5.156 inches **Keying Facility:** Included **Keying Facility Type:** Keyway Web/spoke Relationship To Face Centerline: Offset

Lightening Hole:

Not included

NSN 3020-00-495-9614 Cone Pulley - Page 2 of 2



| Integral Cooling Vane: | |
|-----------------------------------------------------------|--|
| Not included | |
| Groove Shape: | |
| V | |
| Protruding Hub Characteristic: | |
| Plain | |
| Bore Bearing: | |
| Not included | |
| Hub End Outside Diameter And Location: | |
| 1.750 inches aa end | |
| Distance From Outside Flange/rim To Hub End And Location: | |
| 0.250 inches aa end and 0.750 inches bb end | |
| V Groove Pitch Diameter: | |
| 4.562 inches and 4.531 inches | |
| Quantity: | |
| 1 | |
| Surface Treatment: | |
| Oxide | |
| Style Designator: | |
| Webbed or spoked | |
| Surface Treatment: | |
| Black oxide | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| T353-b | |
| | |
| | |