NSN 3020-00-497-1730

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-497-1730
Body Style:
Webbed, with lightening holes
Spline Quantity:
64 both ends
Attachment Method:
Mounting hole
Pitch Diameter:
14.2000 inches
Teeth Quantity:
71
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
4.0000 inches both ends
Mounting Hole Thread Series Designator:
Unf axially through body, first end
Hardness Rating:
58.0 rockwell c and 62.0 rockwell c teeth
Mounting Hole Thread Size:
0.312 inches axially through body, first end
Mounting Hole Type And Quantity:
6 threaded axially through body, first end
Outside Diameter:
14.5025 inches
Tooth Form:
Standard
Pressure Angle:
25.0000 degrees
Face Width:
2.620 inches
Bore Diameter:
4.117 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
5.530 inches first end
Bolt Hole Circle Diameter:
4.874 inches axially through body, first end
Material:
Steel comp 4620 or steel comp 8617h or steel comp 8620h or steel comp 8622h
Material Specification:

Fed standard 66 federal standard all material responses

NSN 3020-00-497-1730

Spur Gear - Page 2 of 2



Sty	υt	-51	u	เลเ	u	I -

Flush hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300